



Features and Controls

- Gooseneck microphone with GSM immunity and LED ring
- High quality loudspeaker
- Microphone on/off button
- Headphone volume control
- The chairman version (FC/M) comes with a priority- and a next-in-line button



Description

The FD/M is a fully integrated delegate panel equipped with loudspeaker, headphone connector and headphone volume control. The included gooseneck microphone is free from interference caused by mobile phones.

It is intended for flush mounting and combines several functionalities in one single panel.

The FD/M is compatible with both the TCS2500 and the TCS5500 conference system. The latter requires the use of additional SPL5525 splitter units.

Specifications

Technical Data	
Dimensions (mm)	245(w) x 105(h) x 43 (d)
Cut-out (mm)	225(w) x 95(h) x 85 (d)
Microphone Length	380 mm
Weight (g)	± 810
Front plate	Steel
Color	RAL 7021 (Matt black)
Part Number	71.60.2201 (Delegate) 71.60.2202 (Chairman)

Accessories

- TEL151 Delegate Headphone (71.04.0151)
- Digital bus cable, RJ45 24AWG:

YPC1	1 m	(71.67.4001)
YPC2	2 m	(71.67.4002)
YPC5	5 m	(71.67.4005)
YPC10	10 m	(71.67.4010)
YPC20	20 m	(71.67.4020)

Standard Ethernet patch cable AWG26 cannot be used!

- SPL5525 for connection to TCS5500 central equipment (71.67.5035)

Connectivity

- Two RJ 45 connectors for separate loop through cabling, max 20 units/branch
- 3,5 mm jack socket for headphone
- Compatible with TCS2500 Central Units
- Compatible with TCS5500 Central Units through SPL5525 interface

Dimensions

