



Features and Controls

- Gooseneck microphone with GSM immunity and LED ring
- High quality loudspeaker
- Microphone on/off button
- Five voting buttons with LED indicators
- Chip card reader/programmer
- Channel selector with volume control
- Two digit LED display for channel and volume information
- The chairman version (FC/MV5BCS) comes with a priority and a next-in-line button



Description

The FD/MV5BCS is a fully integrated delegate panel equipped with loudspeaker, channel selector, headphone connector, five button voting and badge reader.

It is intended for flush mounting and combines several functionalities in one single panel.

The included gooseneck microphone is free from interference caused by mobile phones

The FD/MV5BCS is compatible with both the TCS2500 and the TCS5500 conference system. The latter requires the use of additional SPL5525 splitter units.

Specifications

| Technical Data | |
|-------------------|------------------------------------------------|
| Dimensions (mm) | 245(w) x 105(h) x 43 (d) |
| Cut-out (mm) | 225(w) x 95(h) x 85 (d) |
| Microphone Length | 380 mm |
| Weight (g) | ± 900. |
| Front plate | Steel |
| Color | RAL 7021 (Matt black) |
| Part Number | 71.60.2207 (Delegate) 71.60.2208 (Chairman) |

Accessories

- TEL151 Delegate Headphone (71.04.0151)
- Chip Card (71.43.2000)
- Digital bus cable, RJ45 24AWG:

| | | |
|-------|------|--------------|
| YPC1 | 1 m | (71.67.4001) |
| YPC2 | 2 m | (71.67.4002) |
| YPC5 | 5 m | (71.67.4005) |
| YPC10 | 10 m | (71.67.4010) |
| YPC20 | 20 m | (71.67.4020) |

Standard Ethernet patch cable AWG26 cannot be used!

- SPL5525 for connection to TCS5500 central equipment (71.67.5035)

Connectivity

- Two RJ 45 connectors for separate loop through cabling, max 20 units/branch
- 3,5 mm jack socket for headphone
- Compatible with TCS2500 Central Units
- Compatible with TCS5500 Central Units through SPL5525 interface

Dimensions

