


Controls and Features

- Intended for flush mounting
- Microphone On/Off or request-to-speak button with corresponding LED indicators



Connectivity

- 10-pin shielded modular RJ48 jack
- 5-pin XLR connector for TGM404 gooseneck microphone

Accessories

- Microphone Connection Cable MCC with 2 shielded modular RJ plugs to connect to INT5500 Delegate Controller Interface

Description

The DML5500/XLR Delegate Microphone Panel is intended for flush mounting. It is equipped with a 5 pin locking XLR connector, to receive a removable gooseneck microphone TGM404 (included).

The DML5500/XLR allows participants in a meeting to speak or register a request to speak, and is equipped with a Microphone On/Off or request-to-speak button with corresponding LED indicators.

Custom built versions are available upon request.

MCC5/1	1m	(71.67.5501)
MCC5/2	2m	(71.67.5502)
MCC5/3	3m	(71.67.5503)

Specifications

Technical Data	
Dimensions (mm)	50 (h) x 135 (w)
Cut-out (mm)	43 (h) x 120 (w) approx.
Length Microphone (mm)	+/- 400 (Plugged in and incl windshield)
Weight (g)	+/- 220
Colour	RAL7021 (Matt Black)
Front plate	Steel
Part Number	71.67.5088

Dipswitch Settings

Gain			
Switch 1	Switch 2	Amplification	dBr
0	0	11 (+20.8 dB)	+8,6
0	1	4 (+12.2 dB)	0
1	0	4 (+12.2 dB)	0
1	1	2.8 (+9 dB)	-3,2

Standard setting	
Switch 1	1 (on)
Switch 2	0 (off)
Switch 3	1 (on)
Switch 4	0 (off)

High Pass Filter		
Switch 3	Switch 4	Frequency
0	0	328 Hz
0	1	148 Hz
1	0	226 Hz
1	1	55 Hz