



## Description

The V3B5500 Delegate Voting Panel is intended for flush mounting.

The V3B5500 gives delegates of a conference access to voting and audience interaction facilities. It is equipped with 3 voting buttons with LED indicators and a chip card reader.

The V3B5500 is intended for direct connection to an INT5500 interface.

## Controls and Features

- Intended for flush mounting
- 3 voting buttons with LED indicators. Depending on the mode used these buttons provide different functions
- Identification and access control with integrated chip card reader

*Custom built versions are available upon request.*

## Connectivity

- Two 8-pin shielded modular RJ jacks for connection to the INT5500 and loop-through to a loudspeaker.

## Accessories

- Blank Chip Card CC 5500 (71.43.2000)
- Connection Cable CSC with shielded modular RJ plug to connect to INT5500 Delegate Controller Interface

CSC5/0.5	0.5m	(71.67.5105)
CSC5/1	1m	(71.67.5110)
CSC5/2	2m	(71.67.5120)
CSC5/3	3m	(71.67.5130)



## Specifications

Technical Data	
Dimensions (mm)	50 (h) x 135 (w)
Cut-out (mm)	45 (h) x 120 (w) approx.
Weight (g)	+/- 160
Colour	RAL7021 (Matt Black)
Front plate	Steel
Part Number	71.67.5067

