



## Description

The EU5500 allows extension of the TCS 5500 digital conference system to accommodate more delegate or interpreter units. Up to 8 branches can be connected to the extension unit. Each TMS branch can accommodate up to 40 delegates, each TIS branch can accommodate up to 10 interpreter desks.


Several extension units can be daisy-chained allowing a virtually unlimited number of delegates..

## Controls and Features

- Reset button
- 14 Indicator LEDs for system clock, port activity, power supply, external and info line activity
- 8 DIL Switches + associated indicator LEDs for (de-) activation of the power supply on each branch individually
- One rotary BCD Switch, for ID setting adjustment of extension unit
- One fuse (power supply)

## Connectivity

- Eight 8-pin RJ-45 connectors for connection of branches.
- Two 8-pin RJ-45 connectors for connection from CPU5500 or previous Extension Unit (IN & OUT)
- Two 8-pin RJ-45 connectors for connection to CE5500 clock generator (IN and OUT)
- One Phoenix connector for 48V Power Supply



## Accessoires

- Fully assembled Power Supply Cable, ready for use:  
PW2                      2m                      (71.67.4102)  
(One power supply cable included in the delivery)

## Specifications

Technical Data	
Dimensions (mm)	43 (h) x 483 (w) x 182 (d)
Weight (g)	+/- 2.300
Colour	RAL7021 (Matt Black)
Housing	Metal
Part Number	71.61.5051